

Series HTG2

Programmable Digital Torque Gauge

- Programmable high/low setpoints with color-coded LED indicators and output signal for quick go/no go testing
- 1,000 Data memory for computer download
- lbf-in, kgf-cm, and N-cm units are selectable
- RS-232C, Digimatic and Analog outputs
- Runs on internal NI-MH batteries or AC adapter
- Ergonomic design with non-slip rubber grip, heavy duty metal construction
- Both clockwise and counterclockwise operation
- Overload capacity 200% of F.S.
- Real time and peak mode (selectable)
- Overload alarm and output signal
- Low battery indicator
- 6.5mm Jacobs Chuck (4mm for HTG2-4)(13mm Chuck available)

NEW!
Easy-to-Read
Giant LCD
Display



HTG2 Kit


Ergonomic Design
with Non-Slip
Rubber Grip

HTG2 Ranges (Resolution) Accuracy±0.5% F.S. ±1 LSD

Model	lbf-in	Capacity (Resolution) kgf-cm	N-cm
HTG2-4	70.00 ozf-in (0.01 ozf-in)	5.000 kgf-cm (0.001 kgf-cm)	50.00 N-cm (0.01 N-cm)
HTG2-15	15.00 lbf-in (0.01 lbf-in)	20.00 kgf-cm (0.01 kgf-cm)	200.0 N-cm (0.1 N-cm)
HTG2-40	40.00 lbf-in (0.01 lbf-in)	50.00 kgf-cm (0.01 kgf-cm)	500.0 N-cm (0.1 N-cm)
HTG2-85	85.0 lbf-in (0.1 lbf-in)	100.0 kgf-cm (0.1 kgf-cm)	1000 N-cm (1 N-cm)

Specifications subject to change without notice.

HTG2 digital torque gauges offer programmable high/low setpoints for go/no-go testing. **ORANGE** lights up for measurements less than Low setpoint, **GREEN** for between High and Low setpoint, and **RED** for over High setpoint.



Store up to 1,000 values in memory, which can be displayed or transmitted using serial output. Use the real time mode to display torque transients, or the peak mode to capture the peak torque achieved during a test. Selectable measuring units of lbf-in, kgf-cm, or N-cm.

HTG2 gauges are sold in kits which include the gauge, sensor, six foot cable, and AC adapter/charger. Built-in NI-MH rechargeable batteries.

