

**ProComSol, Ltd**  
*Process Communications Solutions*

**technical**  
**CAL**

[www.technical-sys.com](http://www.technical-sys.com)  
**1-86-MEASURE-1** (1-866-327-0731)

expanding possibilities

# HM-BT-BAT

## HART Modem - Bluetooth

### Benefits:

- Access hard to reach instrumentation from the ground
- Improve plant personnel safety
- Easy instrument configuration using PDA's or PC's without bulky modules or wires
- Less clutter on desk or workbench

### Feature Highlights:

- Bluetooth v1.2
- Reliable wireless communication up to 100 ft (30m)
- Internal antenna
- Battery powered (Standard 9V)
- Integral heavy duty HART Minigrabber connectors
- Meets HART Physical Layer Spec HCF\_SPEC-54
- High security 128 bit encryption
- Compact size 2.5" x 4.25" x 1.25" (64mm x 108mm x 32mm)
- Rugged ABS plastic enclosure
- HART Modem Test Program included for PC and Pocket PC
- 1 Year warranty



[www.technical-sys.com](http://www.technical-sys.com)



**ProComSol, Ltd**  
*Process Communications Solutions*

**technical**

[www.technical-sys.com](http://www.technical-sys.com)  
**1-86-MEASURE-1** (1-866-327-0731)

expanding possibilities

# HM-BT-BAT

## HART Modem - Bluetooth

### Specifications:

#### Enclosure

Material	High strength ABS Plastic
Dimensions	2.5" x 4.25" x 1.25" (64mm x 108mm x 32mm)
Total Unit Weight	6 oz (170 g)

#### Cables

HART Cable Length	4' (1.2 m)
HART Cable Connectors	Mini-Grabber

#### HART

Interface	Capacitive coupling
Output	600 mVpp
Leakage	< 10 uA
Connections	Across loop resistor or HART field device
Specifications	HART 4, HART 5, HART 6, HART 7, HART Physical Layer Spec HCF_SPEC-54

#### Bluetooth

Specifications	Bluetooth v1.2
Frequency	2.4 GHz
Class 1 Master Distance	100' (30m)
Class 2 Master Distance	25' (7.6m)

#### Battery

Type	9V
Life	14 hours continuous use

#### Environmental

Operating Temperature	0 degC to 50 degC (32 degF to 122 degF)
Storage Temperature	-40 degC to 85 degC (-40 degF to 185 degF)
Humidity	0% to 99% (non-condensing)

#### Quality

Warranty	1 Year
----------	--------

[www.technical-sys.com](http://www.technical-sys.com)